

หัวฉีดแบบทั่วไป

Full cone spray nozzle




Features

- Full cone spray pattern with a round impact area
- Uniform distribution
- Easy-to-maintain three-piece type
- X-shaped whirler cone spray largest free passage diameter for minimal clogging
- Various flow rates and spray angles Available



Application

- Pretreatment plant & edp coating plant
- Wet paint spray booth & powder coating booth & asu
- Air supply unit, clean air make up unit
- Cooling out off oven, bake oven, Cure oven, Curing
- Conveyor, monorail, washing spray
- Shower test spray booth, leakage test spray unit




Material

Japan stainless steel sus304

Dimensions

Pipe Diameter (in)	Size (mm)		Weight (g)
	A	B	
1/4	32	10	30
3/8	38	11	50
1/2	49	14	100
3/4	60	17	200



Specification

(in)	Model	Lit / min								Spray					
		0.2 kg/cm ²	0.3 kg/cm ²	0.5 kg/cm ²	0.7 kg/cm ²	1.0 kg/cm ²	1.5 kg/cm ²	2.0 kg/cm ²	2.5 kg/cm ²	3.0 kg/cm ²	4.0 kg/cm ²	5.0 kg/cm ²	7.0 kg/cm ²	10.0 kg/cm ²	
1/4	K7.14.BJ	-	-	1.60/40°	1.90/45°	2.45/50°	3.20/55°	3.60/55°	3.90/55°	4.20/55°	4.63/50°	5.00/50°	6.00/50°	6.50/45°	
	K7.14.BD	-	1.60/40°	2.00/45°	2.40/50°	2.90/55°	3.60/55°	4.30/60°	4.90/60°	5.40/60°	6.20/55°	6.90/50°	8.20/50°	9.40/45°	
	K7.14.BF	1.80/45°	2.20/50°	2.70/55°	3.10/55°	3.65/60°	4.45/60°	5.20/60°	5.90/60°	6.50/60°	7.50/60°	8.40/50°	10.05/50°	11.40/50°	
	K7.14.CB	2.60/45°	3.00/50°	3.80/55°	4.40/55°	5.20/60°	6.40/60°	7.40/60°	8.20/60°	8.80/60°	10.00/60°	11.00/55°	13.20/50°	14.80/50°	
3/8	K7.38.BH	2.10/40°	2.70/40°	3.30/45°	3.80/45°	4.50/50°	5.40/50°	6.20/50°	6.80/50°	7.40/50°	8.40/45°	9.25/45°	11.00/45°	12.40/40°	
	K7.38.CB	3.40/40°	4.00/45°	4.80/50°	5.30/50°	6.20/55°	7.30/55°	8.40/55°	9.30/55°	10.00/55°	11.20/50°	12.30/50°	14.60/46°	16.60/45°	
	K7.38.CF	4.00/40°	4.60/45°	5.50/55°	6.30/55°	7.60/60°	9.20/60°	10.60/60°	11.80/60°	12.60/60°	14.00/55°	15.30/53°	18.20/50°	21.00/47°	
	K7.38.DJ	4.90/40°	6.00/50°	7.45/55°	8.40/60°	9.80/60°	12.00/65°	13.60/70°	14.60/70°	15.40/70°	17.30/65°	18.80/60°	22.00/55°	24.80/50°	
	K7.38.DH	6.10/40°	7.30/45°	8.90/60°	10.50/65°	12.90/70°	15.20/80°	17.05/85°	18.50/85°	19.60/85°	21.20/80°	23.00/80°	26.60/70°	29.60/70°	
1/2	K7.12.DH	7.00/40°	8.20/40°	10.50/45°	12.30/50°	14.40/60°	17.20/65°	19.20/65°	20.80/65°	22.40/65°	25.40/60°	28.00/55°	33.00/50°	37.00/50°	
	K7.12.EE	7.90/40°	9.10/40°	11.50/45°	13.40/50°	16.30/60°	19.50/65°	21.80/65°	24.00/65°	26.20/65°	29.40/60°	32.40/55°	38.50/50°	44.00/50°	
	K7.12.FJ	8.80/45°	10.20/50°	12.90/60°	15.00/60°	17.90/65°	21.80/70°	24.60/75°	27.00/75°	28.70/75°	32.30/70°	35.90/65°	43.60/60°	50.10/60°	
	K7.12.FD	9.40/50°	11.40/50°	13.60/60°	15.40/65°	18.50/70°	22.60/80°	25.20/85°	28.30/85°	30.10/85°	34.80/80°	38.40/75°	46.40/70°	53.00/70°	
3/4	K7.34.FD	10.00/60°	13.20/60°	16.40/60°	19.20/60°	22.90/65°	27.00/70°	30.30/70°	32.50/70°	35.80/70°	40.00/65°	43.80/65°	53.00/60°	60.00/60°	
	K7.34.GE	12.00/60°	16.60/60°	21.50/60°	24.40/65°	28.20/70°	35.20/75°	40.30/75°	43.80/75°	47.00/75°	53.00/70°	58.40/70°	70.00/65°	80.00/50°	
	K7.34.IJ	17.00/60°	22.00/60°	26.00/65°	30.00/70°	36.00/75°	45.00/80°	49.80/85°	54.40/85°	58.80/85°	67.50/80°	74.50/75°	89.00/70°	100.00/70°	

* K7 Nozzles thread available : 1/4", 3/8", 1/2", 3/4"