

Feature


Suited for CIP systems. No motor source is needed due to the reaction force of the cleaning liquid to rotate spray head. Low pressure for cleaning and rinsing application. For rinsing small and medium sized vessels for example dairy, chemical, pharmaceutical and food industries. Material of construction-corrosion-resistance (PTFE)



Application

- Tank Washing (Max Ø 3 m)
- Rinsing vessels
- Corrosion resistance

Dimension



Spray Angle

Coverage Type			
Spray Angle	270°	270°	360°



Model	Spray Code	Angle Code	Thread Size	Spray Capacity (L/min) At Pressure (Bar)						
				1.5	2	3	5	7	H	D
TC-RED	2.300	C/D/E	3/4"	27.71	32.00	39.19	50.60	59.87	100	70
	2.520	C/D/E	3/4"	45.03	52.00	63.69	82.22	97.28		
	2.720	C/D/E	3/4"	62.35	72.00	88.18	113.84	134.70	Weight (Metals) 562.0 gms. Approx	
	2.950	C/D/E	3/4"	82.27	95.00	116.35	150.21	177.73		
	3.140	C/D/E	3/4"	121.24	140.0	171.46	221.36	261.92		

How to order (Example)

TC-RED

Model

2.300

Spray Code

C

Angle Code

3/4"

Thread Size

S304

Material

Material Available :
Stainless Steel : S304, S316