

Pipe Cleaning

Stainless steel spinning nozzles.



Application

- for removal of grease and limestone from pipe walls
- cleaning of wells and boreholes
- pipe cleaning before CCTV inspection



Tremol 3/8"

	1/8" F	1/4" F	3/8" F	1/2" F, 1/2" M	3/4" F	1" F	1" 1/4 F
Ø x L (mm)	16 x 27	20 x 35	35 x 60	35 x 60	50 x 83	70 x 105	70 x 105
Weight (kg)	30 gr	0,1	0,3	0,3	0,8	2,6	2,6
Jet angle							
rotation/break	90°/85°	90°/85°	90°/85°	90°/85°	90°/85°	90°/85°	90°/85°
rear	20°	20°	20°	20°	20°	20°	20°
Inserts	-	-	10 x M4	10 x M4	10 x M6 ^(*)	10 x M6 ^(*)	10 x M6 ^(*)
Flow (lt/min)	>25	>30	>40	>40	>70	>100	>100
Max pressure (bar)	275	275	275	275	275	275	275
Working DN (mm)	20-60	30-60	50-150	50-150	100-300	150-400	150-400

75510.190R 75510.230R 75510.12R 75510.14R 75510.35R 75510.250R 75510.27R
75510.14M

(*) M6 Hex head ceramic inserts